



Anaconda Robust W4



Anaconda Robust W4 are heavy duty clamps specially designed for high loads and corrosive environments. Best suited for mid to high pressure applications and hard hoses, or for fitting metal pipes, such as Automotive Exhaust pipes. Material: stainless chromium-nickel steel (17-20% chromium, 9-12% nickel) AISI 304, DIN 1.4301.

Diameter (mm)	Screw thread x length (mm)	Band Width & Thickness (mm)	Free Torque (Nm)	Loading Torque (Nm)
17-19	M5x40	18*0.6	≤1.0	≥7.0
20-22	M5x40	18*0.6	≤1.0	≥7.0
23-25	M5x40	18*0.6	≤1.0	≥7.0
26-28	M5x40	18*0.6	≤1.0	≥7.0
29-31	M6x50	20*0.6	≤1.0	≥13.0
32-35	M6x50	20*0.6	≤1.0	≥13.0
36-39	M6x50	20*0.6	≤1.0	≥13.0
40-43	M6x50	20*0.6	≤1.0	≥13.0
44-47	M6x55	22*0.8	≤1.0	≥13.0
48-51	M6x55	22*0.8	≤1.0	≥13.0
52-55	M6x55	22*0.8	≤1.0	≥13.0
56-59	M6x55	22*0.8	≤1.0	≥13.0
60-63	M6x55	22*0.8	≤1.0	≥13.0
64-67	M6x55	22*0.8	≤1.0	≥13.0
68-73	M8x70	24*0.8	≤1.0	≥25.0
74-79	M8x70	24*0.8	≤1.0	≥25.0
80-85	M8x70	24*0.8	≤1.0	≥25.0
86-91	M8x70	24*0.8	≤1.0	≥25.0
92-97	M8x70	24*0.8	≤1.0	≥25.0
98-103	M8x70	24*0.8	≤1.0	≥25.0
104-112	M8x80	24*0.8	≤1.0	≥25.0
113-121	M8x80	24*0.8	≤1.0	≥25.0
122-130	M8x80	24*0.8	≤1.0	≥25.0
131-139	M10x90	26*1.0	≤1.0	≥40.0
140-148	M10x90	26*1.0	≤1.0	≥40.0
149-161	M10x110	26*1.0	≤1.0	≥40.0
162-174	M10x110	26*1.0	≤1.0	≥40.0



Diameter (mm)	Screw thread x length (mm)	Band Width & Thickness (mm)	Free Torque (Nm)	Loading Torque (Nm)
175-187	M10x110	26*1.0	≤1.0	≥40.0
188-200	M10x110	26*1.0	≤1.0	≥40.0
201-213	M10x110	26*1.0	≤1.0	≥40.0
214-226	M10x110	26*1.0	≤1.0	≥40.0
227-239	M10x110	26*1.0	≤1.0	≥40.0
240-252	M10x110	26*1.0	≤1.0	≥40.0
253-265	M10x110	26*1.0	≤1.0	≥40.0
266-278	M10x110	26*1.0	≤1.0	≥40.0
279-291	M10x110	26*1.0	≤1.0	≥40.0
294-304	M10x110	26*1.0	≤1.0	≥40.0

